



Product Service

CERTIFICATE

No. Z1A 029312 0035 Rev. 00

Certificate Holder: KEMMLIT-Bauelemente GmbH

Maltschachstr. 37
72144 Dußlingen
GERMANY

Test Mark:



Product:

**Space Partitioning Elements
Partition Wall System
for public sanitary areas**

Tested according to:

PPP 52192C:2024
AfPS GS 2019:01 PAK

With this certificate, the GS body of TÜV SÜD Product Service GmbH, within the scope of its designation, grants the named certificate holder for the designated product with the specified model designation the GS mark according to § 20 ProdSG. The product complies with the requirements of § 20 para. 3 ProdSG regarding the assurance of safety and health. Attention is drawn to the obligations of the manufacturer according to § 24 ProdSG. The certified product can be marked with the test marks shown above. Any alteration of the presentation of the test marks is not permitted. The transfer of a certificate by the certificate holder to third parties is not permissible. The certificate is valid until the specified date, unless it is terminated earlier. All applicable requirements of the testing, certification, validation, and verification regulations of the TÜV SÜD Group must be fulfilled. For details, please see: www.tuvsud.com/ps-zert

Report No.:

713374868-2 Rev. 01

Valid until:

2030-10-19

Date, 2025-10-20

(Jens Biesenack)

CERTIFICATE

No. Z1A 029312 0035 Rev. 00

Model(s): **variocell**
 softcell
 hardcell
 classiccell

Specifications:

Door / Wall Material	42 mm steel composite elements Aluminum or stainless steel
classiccell	
Overall Height	2000 mm or 2135 mm incl. 150 mm floor clearance up to 2800 mm without floor clearance
Cubicle Depth	1500 mm (from 1601 mm with joint and foot)
Door Width	570 mm (nominal dimension) 650 mm (nominal dimension=standard) 750 mm (nominal dimension) 980 mm (nominal dimension)
softcell, hardcell	
Overall Height	2000 mm or 2135 mm including 150 mm floor clearance (-10 / + 25 mm) up to 2800 mm without floor clearance
Cubicle Depth	up to 1600 mm divided with shadow gap from 1601 mm divided with shadow gap joint and additional foot
Door Width	from 570 - 980 mm (nominal dimension)
variocell	
Overall Height	2000 mm or 2135 mm incl. 150 mm floor clearance up to 2800 mm without floor clearance
Cubicle Depth	1500 mm (1601 mm with joint and foot)
Door Width	570 mm (nominal dimension) 650 mm (nominal dimension=standard) 750 mm (nominal dimension) 980 mm (nominal dimension)