



Product Service

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Certificate Holder: KEMMLIT-Bauelemente GmbH

Maltschachstr. 37
72144 Dußlingen
GERMANY

Certification Mark:



Product:

**Room Partitioning Elements
Partition Wall Systems in Sanitary Rooms**

Certified according to:

PPP 52192B:2020
AfPS GS 2019:01 PAK

With this certificate, the GS body of TÜV SÜD Product Service GmbH, within the scope of its appointment, grants the aforementioned certificate holder for the designated product with the specified model designation the GS mark according to § 20 ProdSG. The product complies with the guarantee of safety and health with the requirements of § 20 Para. 3 ProdSG. Attention is drawn to the obligations of the manufacturer according to § 24 ProdSG. The certified product can be marked with the test marks shown above. Any alteration of the representation of the test marks is not permitted. The transfer of a certificate by the certificate holder to third parties is inadmissible. The certificate is valid until the specified date, unless it is terminated earlier. All applicable requirements of the Testing and Certification Regulations of the TÜV SÜD Group must be fulfilled. For details, please see: www.tuvsud.com/ps-zert

Report No.:

713254444-2

Valid until:

2027-07-27

Date, 2022-07-29

(Ulrich Sommer)

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Model(s):

B-Bambino-Exklusiv
 B-Bambino Klassik
 D-Bambino Klassik
 BK-E-Bambino-Exklusiv
 BK-E Bambino Klassik
 DK-E-Bambino Klassik

Specifications:

General

System height: 1400 mm (B-Bambino-Exklusiv, B-Bambino Klassik, D-Bambino Klassik),

1970 mm for adults (BK-E-Bambino-Exklusiv, BK-E Bambino Klassik, DK-E Bambino Klassik)

Door widths: 470 mm, 520 mm, 570 mm (standard), 900 mm, opening outwards

Cubicle depth: 1100 mm (standard dimension)

Fittings: 3-roller safety spring hinge, Ø 20 mm, with continuous aluminum finger protection tube between the hinges.

Door handles: Safety ring handle made of impact and break-resistant nylon with integrated rubber damper as a door stop.

Feet: Ø 20 mm, height-adjustable, made of powder-coated aluminum with stainless steel plate and tread-resistant cover rosette made of nylon

Wall connections: Wall connections via sturdy aluminum plate holders, powder-coated or anodized, for compensating construction tolerances.

Types B-Bambino-Exklusiv and BK-E-Bambino-Exklusiv

Walls: 13 mm thick HPL solid core panels according to DIN EN 438 series (DIN 16926). The corners are rounded to a radius of 6 mm to prevent injuries.

Doors: Of the same construction as the walls, with safety finger protection, made of a continuous 20 mm wide soft-lip finger protection profile on the closing side and a continuous aluminum finger protection tube on the hinge side. Swing doors are not permitted.
Door opening only outwards

Ground clearance: 80 mm

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Types B-Bambino Klassik and BK-E Bambino Klassik

Walls: 13 mm thick HPL solid core panels according to DIN EN 438 series (DIN 16926). The corners, to prevent injuries, are rounded with a radius of 33 mm

Doors: Of the same construction as the walls, with safety finger protection, made of a continuous 20 mm wide soft-lip finger protection profile on the strike side and a continuous aluminum finger protection tube on the hinge side. Swing doors are not permitted. Door opening only outwards.

Ground clearance: 120 mm or 89 mm

Types D-Bambino Klassik and DK-E-Bambino Klassik

Walls: 30 mm thick melamine resin-coated solid chipboard panels. All edges are protected against impact with 2 mm thick ABS edgings (radius = 2mm). All corners, to prevent injuries, are rounded with a radius of 33 mm.

Doors: Of the same construction as the walls, with safety finger protection, made of a 20 mm wide rounded soft-lip finger protection on the strike side and a continuous aluminum finger protection tube on the hinge side. Swing doors are not permitted. Door opening only outwards.

Ground clearance: 120 mm or 89 mm