



Product Service

CERTIFICATE

No. Z1A 029312 0032 Rev. 00

Certificate Holder: KEMMLIT-Bauelemente GmbH

Maltschachstr. 37
72144 Dußlingen
GERMANY

Certification Mark:



Product:

**Room Partition Elements
Partition Wall Systems in Sanitary Rooms**

Tested according to:

PPP 52192B:2020
AfPS GS 2019:01 PAK

With this certificate, the GS body of TÜV SÜD Product Service GmbH, within the scope of its designation, grants the GS mark according to § 20 ProdSG to the named certificate holder for the designated product with the specified model designation. The product complies with the requirements of § 20 Abs. 3 ProdSG regarding the guarantee of safety and health. Attention is drawn to the obligations of the manufacturer according to § 24 ProdSG. The certified product can be marked with the certification marks shown above. Any alteration of the representation of the certification marks is not permitted. The transfer of a certificate by the certificate holder to third parties is inadmissible. The certificate is valid until the specified date, unless it is terminated earlier. All applicable requirements of the Testing and Certification Regulations of the TÜV SÜD Group must be met. For details, please see: www.tuvsud.com/ps-zert

Report No.:

713254444-1

Valid until:

2027-07-27

Date, 2022-07-29

(Ulrich Sommer)

CERTIFICATE

No. Z1A 029312 0032 Rev. 00

Model(s): **NiUU one**
 NiUU F
 NiUU K

Specifications:

NiUU F	
Door / Wall material	Melamine resin-coated wood-based panel, Material thickness 30 mm
Door closing type	Rebated, flush-closing with solid aluminum edge
Door height	System height 2135 mm with 150 mm floor clearance (for full-height version with top panel)
System height	2135 mm; special heights max 2800 mm
Cubicle depth	1500 mm (nominal dimension)
Door width	570 mm (nominal dimension) 650 mm (nominal dimension) 750 mm (nominal dimension) 980 mm (nominal dimension) Special widths possible

NiUU K	
Door/Wall material	Melamine resin-coated wood-based panel Material thickness 38 mm Intermediate walls 30 mm
Door closing type	Rebated, flush-closing with solid aluminum edge
Door height	System height 2135 mm with 150 mm floor clearance (for full-height version max. 2800 mm)
System height	2135 with 150 mm floor clearance (for full-height version max. 2800 mm)
Cubicle depth	1500 mm (nominal dimension)
Door width	570 mm (nominal dimension) 650 mm (nominal dimension) 750 mm (nominal dimension) 980 mm (nominal dimension)

CERTIFICATE

No. Z1A 029312 0032 Rev. 00

NiUU one F & NiUU one K	
Door / wall material for NiUU one F, material thickness 30 mm, Intermediate walls 30 mm or composite panel	Wood-based panel, melamine resin coated,
Door / wall material for NiUU one K, material thickness 38 mm, Intermediate walls 30 mm	Wood-based panel, melamine resin coated,
Door stop	Flush-closing, with ABS edge
System height	2000 mm including 150 mm floor clearance Special heights max. up to 2800 mm
Cubicle depth	1500 mm (nominal dimension)
Door width	570 mm (nominal dimension) 640 mm (nominal dimension) 750 mm (nominal dimension) 980 mm (nominal dimension)